

## Contents

<b>1</b>	<b>Format specifications</b>	<b>2</b>
<b>2</b>	<b>Formatting various data-types</b>	<b>3</b>
<b>3</b>	<b>Possibilities, and things to do</b>	<b>3</b>
	<b>Index</b>	<b>3</b>

# The l3str-format package: formatting strings of characters\*

The L<sup>A</sup>T<sub>E</sub>X3 Project<sup>†</sup>

Released 2016/06/13

## 1 Format specifications

In this module, we introduce the notion of a string  $\langle format \rangle$ . The syntax follows that of Python's `format` built-in function. A  $\langle format specification \rangle$  is a string of the form

$$\langle format specification \rangle = [[\langle fill \rangle] \langle alignment \rangle][\langle sign \rangle][\langle width \rangle][.\langle precision \rangle][\langle style \rangle]$$

where each  $[...]$  denotes an independent optional part.

- $\langle fill \rangle$  can be any character: it is assumed to be present whenever the second character of the  $\langle format specification \rangle$  is a valid  $\langle alignment \rangle$  character.
- $\langle alignment \rangle$  can be `<` (left alignment), `>` (right alignment), `^` (centering), or `=` (for numeric types only).
- $\langle sign \rangle$  is allowed for numeric types; it can be `+` (show a sign for positive and negative numbers), `-` (only put a sign for negative numbers), or a space (show a space or a `-`).
- $\langle width \rangle$  is the minimum number of characters of the result: if the result is naturally shorter than this  $\langle width \rangle$ , then it is padded with copies of the character  $\langle fill \rangle$ , with a position depending on the choice of  $\langle alignment \rangle$ . If the result is naturally longer, it is not truncated.
- $\langle precision \rangle$ , whose presence is indicated by a period, can have different meanings depending on the type.
- $\langle style \rangle$  is one character, which controls how the given data should be formatted. The list of allowed  $\langle styles \rangle$  depends on the type.

The choice of  $\langle alignment \rangle =$  is only valid for numeric types: in this case the padding is inserted between the sign and the rest of the number.

---

\*This file describes v6589, last revised 2016/06/13.

<sup>†</sup>E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

## 2 Formatting various data-types

<hr/>	
<code>\tl_format:Nn</code> ★	<code>\tl_format:nn {&lt;token list&gt;} {&lt;format specification&gt;}</code>
<code>\tl_format:cn</code> ★	
<code>\tl_format:nn</code> ★	Converts the <i>&lt;token list&gt;</i> to a string according to the <i>&lt;format specification&gt;</i> . The <i>&lt;style&gt;</i> , if present, must be <i>s</i> . If <i>&lt;precision&gt;</i> is given, all characters of the string representation of the <i>&lt;token list&gt;</i> beyond the first <i>&lt;precision&gt;</i> characters are discarded.
<hr/>	
<code>\seq_format:Nn</code> ★	<code>\seq_format:nn {&lt;sequence&gt;} {&lt;format specification&gt;}</code>
<code>\seq_format:cn</code> ★	Converts each item in the <i>&lt;sequence&gt;</i> to a string according to the <i>&lt;format specification&gt;</i> , and concatenates the results.
<hr/>	
<code>\int_format:nn</code> ★	<code>\int_format:nn {&lt;intexpr&gt;} {&lt;format specification&gt;}</code>
	Evaluates the <i>&lt;integer expression&gt;</i> and converts the result to a string according to the <i>&lt;format specification&gt;</i> . The <i>&lt;precision&gt;</i> argument is not allowed. The <i>&lt;style&gt;</i> can be <i>b</i> for binary output, <i>d</i> for decimal output (this is the default), <i>o</i> for octal output, <i>X</i> for hexadecimal output (using capital letters).
<hr/>	
<code>\fp_format:nn</code> ★	<code>\fp_format:nn {&lt;fpexpr&gt;} {&lt;format specification&gt;}</code>
	Evaluates the <i>&lt;floating point expression&gt;</i> and converts the result to a string according to the <i>&lt;format specification&gt;</i> . The <i>&lt;precision&gt;</i> defaults to 6. The <i>&lt;style&gt;</i> can be <ul style="list-style-type: none"> <li>• <i>e</i> for scientific notation, with one digit before and <i>&lt;precision&gt;</i> digits after the decimal separator, and an integer exponent, following <i>e</i>;</li> <li>• <i>f</i> for a fixed point notation, with <i>&lt;precision&gt;</i> digits after the decimal separator and no exponent;</li> <li>• <i>g</i> for a general format, which uses style <i>f</i> for numbers in the range <math>[10^{-4}, 10^{&lt;precision&gt;})</math> and style <i>e</i> otherwise.</li> </ul>

## 3 Possibilities, and things to do

- Provide a token list formatting *<style>* which keeps the last *<precision>* characters rather than the first *<precision>*.

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

### F

fp commands:

`\fp_format:nn` ..... *3, 3*

### I

int commands:

`\int_format:nn` ..... *3, 3*

	S		T
seq commands:		tl commands:	
		\tl_format:Nn	..... 3
\seq_format:Nn	..... 3, 3	\tl_format:nn	..... 3, 3